## ACM 18 ANALYTIC CENTER MOBIL





Extraction system in the second generation. Latest state-of-the-art technology for the inspection of Technical Cleanliness on functionally relevant components. Re-engineered in accordance with the recommendations of VDA 19.1 chapter 11 for work safety and protection of the environment. The ACM18 is perfectly suitable for your requirements in future.



## **ACM 18**

SOME HIGHLIGHTS





SUPPLYING of filtered air passes over the flow cap top. Active protection of components and the flushing bowl against contamination. This produces an ISO 5-class like extraction area. High occuptional safety by connecting your extraction to our cabinet.



ANALYSIS BASIN (600 x 750 mm) with polished stainless steel interior. For components up to 15 kg. Smallest parts with high requirements can be tested with optional funnel. Extraction in the front work area.



OPTIONAL INTERNAL FLUSH: Ideal and unique possibility on the market to test interior geometries and surfaces. Completely closed flushing circle with separate membrane holder.



12" BASIC TOUCHSCREEN with intuitively operable software. Simple operating due to password-secured user-levels and the possibility to save test processes. Continuous monitoring of safety relevant functions. Optional comfort touch panel with separate keyboard with easy to clean glass surface available.



THE USER-FRIENDLY, lifting and tilting membrane holder includes three individual cascade rings with tweezer leads for safe and simple membrane fitting and removal of Ø 47 mm membrane filters.



EXTENSIVE CONCEPT OF EXPLOSION PROTECTION:

Prevention of explosive atmosphere in analysis area due to numerous measures: secured ignition protection, separate safety control, high safety technique above the standard, ground connections and much more.



## 元利儀器股份有限公司

台北市內湖區陽光街365巷39號6樓 TFL:886(2)8751-2222 FAX:886(2

TEL:886(2)8751-2222 FAX:886(2)8751-5356

台中市西屯區文心路三段447號23樓-1 TEL:886(4)2293-3161 FAX:886(4)2297-3049 高雄市苓雅區中正一路120號14樓-2 TEL:886(7)716-1295 FAX:886(7)716-3827

