

# **N620**

奈米鎢鋼銑刀 (高速高硬系列)

*Nano Carbide End Mills*  
(Ultra Hard Series)



# N620 奈米鎢鋼平銑刀- 短刃型- 2刃

N620 NANO CARBIDE END MILLS- Square Type- Short Flute- 2F with corner radii



· NESDM20000A

· NESD20000A

| d(刃徑)                 | Tolerance(公差) |
|-----------------------|---------------|
| $\phi < 3$            | 0 ~ -0.015    |
| $3 \leq \phi \leq 10$ | 0 ~ -0.03     |
| $10 < \phi$           | 0 ~ -0.03     |

| R(半徑) | Tolerance(公差) |
|-------|---------------|
| R     | $\pm 0.02$    |

|                      |   |
|----------------------|---|
| 超精銑 Bright Finishing | — |
| 精銑 Finishing         | ○ |
| 中銑 Semi Finishing    | ◎ |
| 粗銑 Roughing          | ◎ |



| 刃徑<br>d | 刃長<br>L1 | 有效長<br>L2 | R角<br>R | 全長<br>L | 柄徑<br>D | 刃數<br>F | 鍍膜訂購編號<br>Coated Order No. |
|---------|----------|-----------|---------|---------|---------|---------|----------------------------|
| 1.0     | 1.0      | 2.0       | 0.1R    | 50      | 4       | 2       | NESDM20100A                |
| 2.0     | 2.0      | 4.0       | 0.1R    | 50      | 4       | 2       | NESDM20200A                |
| 3.0     | 3.0      | 6.0       | 0.1R    | 50      | 4       | 2       | NESDM20300A                |
| 4.0     | 4.0      | 8.0       | 0.2R    | 50      | 4       | 2       | NESDM20400A                |
| 6.0     | 6.0      | 12.0      | 0.2R    | 50      | 6       | 2       | NESD20600A                 |
| 8.0     | 8.0      | 16.0      | 0.3R    | 60      | 8       | 2       | NESD20800A                 |
| 10.0    | 10.0     | 20.0      | 0.3R    | 75      | 10      | 2       | NESD21000A                 |
| 12.0    | 12.0     | 24.0      | 0.3R    | 75      | 12      | 2       | NESD21200A                 |

# N620 奈米鎢鋼平銑刀- 短刃型- 3刃



N620 NANO CARBIDE END MILLS- Square Type- Short Flute- 3F with corner radii

· NESD30000A

| d(刃徑)                 | Tolerance(公差) |
|-----------------------|---------------|
| $\phi < 3$            | 0 ~ -0.015    |
| $3 \leq \phi \leq 10$ | 0 ~ -0.03     |
| $10 < \phi$           | 0 ~ -0.03     |

| R(半徑) | Tolerance(公差) |
|-------|---------------|
| R     | $\pm 0.02$    |

|                      |   |
|----------------------|---|
| 超精銑 Bright Finishing | — |
| 精銑 Finishing         | ◎ |
| 中銑 Semi Finishing    | ◎ |
| 粗銑 Roughing          | ○ |



| 刃徑<br>d | 刃長<br>L1 | 有效長<br>L2 | R角<br>R | 全長<br>L | 柄徑<br>D | 刃數<br>F | 鍍膜訂購編號<br>Coated Order No. |
|---------|----------|-----------|---------|---------|---------|---------|----------------------------|
| 3.0     | 3.0      | 9.0       | 0.1R    | 50      | 6       | 3       | NESD30300A                 |
| 4.0     | 4.0      | 12.0      | 0.2R    | 50      | 6       | 3       | NESD30400A                 |
| 6.0     | 6.0      | 18.0      | 0.2R    | 50      | 6       | 3       | NESD30600A                 |
| 8.0     | 8.0      | 24.0      | 0.3R    | 60      | 8       | 3       | NESD30800A                 |
| 10.0    | 10.0     | 30.0      | 0.3R    | 75      | 10      | 3       | NESD31000A                 |
| 12.0    | 12.0     | 36.0      | 0.3R    | 75      | 12      | 3       | NESD31200A                 |

→ 切削條件表  
Cutting Condition P.282,283

→ 參考資料  
Technical Data P.243

# N620 奈米鎢鋼平銑刀- 短刃型- 4刃

N620 NANO CARBIDE END MILLS- Square Type- Short Flute- 4F with corner radii


· NESDM40000A

· NESD40000A

| d(刃徑)                 | Tolerance(公差) |
|-----------------------|---------------|
| $\phi < 3$            | 0 ~ -0.015    |
| $3 \leq \phi \leq 10$ | 0 ~ -0.03     |
| $10 < \phi$           | 0 ~ -0.03     |

| R(半徑) | Tolerance(公差) |
|-------|---------------|
| R     | $\pm 0.02$    |

|                      |   |
|----------------------|---|
| 超精銑 Bright Finishing | — |
| 精銑 Finishing         | ◎ |
| 中銑 Semi Finishing    | ○ |
| 粗銑 Roughing          | ○ |



| 刃徑<br>d | 刃長<br>L1 | 有效長<br>L2 | R角<br>R | 全長<br>L | 柄徑<br>D | 刃數<br>F | 鍍膜訂購編號<br>Coated Order No. |
|---------|----------|-----------|---------|---------|---------|---------|----------------------------|
| 1.0     | 1.0      | 2.0       | 0.1R    | 50      | 4       | 4       | NESDM40100A                |
| 1.5     | 1.5      | 3.0       | 0.1R    | 50      | 4       | 4       | NESDM40150A                |
| 2.0     | 2.0      | 4.0       | 0.1R    | 50      | 4       | 4       | NESDM40200A                |
| 2.5     | 2.5      | 5.0       | 0.1R    | 50      | 4       | 4       | NESDM40250A                |
| 3.0     | 4.0      | 8.0       | 0.1R    | 50      | 6       | 4       | NESD40300A                 |
| 4.0     | 5.0      | 10.0      | 0.2R    | 50      | 6       | 4       | NESD40400A                 |
| 5.0     | 7.0      | 14.0      | 0.2R    | 50      | 6       | 4       | NESD40500A                 |
| 6.0     | 8.0      | 16.0      | 0.2R    | 50      | 6       | 4       | NESD40600A                 |
| 8.0     | 12.0     | 24.0      | 0.3R    | 60      | 8       | 4       | NESD40800A                 |
| 10.0    | 16.0     | 32.0      | 0.3R    | 75      | 10      | 4       | NESD41000A                 |
| 12.0    | 18.0     | 36.0      | 0.3R    | 75      | 12      | 4       | NESD41200A                 |

# N620 奈米鎢鋼平銑刀- 高導短刃型- 6刃



N620 NANO CARBIDE END MILLS- Square Type- High Helix- Short Flute- 6F with corner radii

· NEHD60000A

| d(刃徑)                 | Tolerance(公差) |
|-----------------------|---------------|
| $\phi < 3$            | 0 ~ -0.015    |
| $3 \leq \phi \leq 10$ | 0 ~ -0.03     |
| $10 < \phi$           | 0 ~ -0.03     |

| R(半徑) | Tolerance(公差) |
|-------|---------------|
| R     | $\pm 0.02$    |

|                      |   |
|----------------------|---|
| 超精銑 Bright Finishing | ○ |
| 精銑 Finishing         | ◎ |
| 中銑 Semi Finishing    | ○ |
| 粗銑 Roughing          | — |



| 刃徑<br>d | 刃長<br>L1 | 有效長<br>L2 | R角<br>R | 全長<br>L | 柄徑<br>D | 刃數<br>F | 鍍膜訂購編號<br>Coated Order No. |
|---------|----------|-----------|---------|---------|---------|---------|----------------------------|
| 6.0     | 9.0      | 15.0      | 0.2R    | 50      | 6       | 6       | NEHD60600A                 |
| 8.0     | 12.0     | 20.0      | 0.3R    | 60      | 8       | 6       | NEHD60800A                 |
| 10.0    | 15.0     | 25.0      | 0.3R    | 75      | 10      | 6       | NEHD61000A                 |
| 12.0    | 18.0     | 30.0      | 0.3R    | 75      | 12      | 6       | NEHD61200A                 |
| 16.0    | 24.0     | 40.0      | 0.5R    | 100     | 16      | 6       | NEHD61600A                 |
| 20.0    | 30.0     | 50.0      | 0.5R    | 100     | 20      | 6       | NEHD62000A                 |

→ 切削條件表  
Cutting Condition P.283,284

→ 參考資料  
Technical Data P.243















